




Teknik Bilgiler / Technical Informations

Thread size / Anma çapı (d)		M2	M2.5	M3	M4	M5	M6	M8	M10
Head height / Kafa yüksekliği k	max.	1,20	1,50	1,65	2,20	2,50	3,00	4,00	5,00
Head dia / Kafa çapı d ²	min.	3,50	4,40	5,30	7,14	8,84	10,57	14,07	17,27
	max.	3,80	4,70	5,60	7,50	9,20	11,00	14,50	18,00
	max.	0,80	0,90	1,00	1,40	1,60	2,00	2,50	3,00
a	m	2,35	2,70	2,90	4,40	4,60	6,60	8,70	9,60
	min.	0,95	1,25	1,50	1,90	2,10	2,80	3,90	4,80
PH	max.	1,25	1,55	1,80	2,40	2,60	3,30	4,40	5,30
	m	2,20	2,50	2,80	4,00	4,40	6,10	8,50	9,40
	min.	0,92	1,22	1,48	1,60	2,05	2,46	3,86	4,77
PZ	max.	1,17	1,47	1,78	2,05	2,51	2,92	4,32	5,23

Thread size Anma çapı			M2	M2.5	M3	M4	M5	M6	M8	M10
Length / Boy	min.	max.	Weight /Ağırlık gr/p							
5	4,75	5,25	0,14	0,24	0,34	0,68				
6	5,75	6,25	0,15	0,27	0,38	0,75	1,21			
8	7,70	8,30	0,19	0,33	0,47	0,90	1,45	2,19		
10	9,70	10,30	0,23	0,39	0,56	1,06	1,70	2,54	5,03	
12	11,65	12,35	0,27	0,45	0,64	1,22	1,95	2,89	5,67	9,59
16	15,65	16,35	0,34	0,57	0,82	1,53	2,44	3,61	6,94	11,80
20	19,60	20,40	0,42	0,69	1,00	1,84	2,94	4,31	8,21	13,80
25	24,60	25,40		0,84	1,22	2,22	3,55	5,19	9,79	16,10
30	29,60	30,40			1,44	2,61	4,16	6,08	11,70	16,80
35	34,50	35,50				2,99	4,76	6,96	13,00	21,10
40	39,50	40,50				3,36	5,39	7,84	14,60	23,60
45	44,50	45,50					6,02	8,73	16,20	26,70
50	49,50	50,50					6,65	9,61	17,90	28,80
55	54,00	56,00							19,40	31,10
60	59,00	61,00								33,20

Değerler milimetre olarak verilmiştir.



SEMVIDA
"Güçlü Bağlantılar,,